

ABOVE-GROUND AUTOMATIC SLATTED COVER

ROLLEASY 2





Simplicity by excellence



ABOVE-GROUND AUTOMATIC SLATTED COVER ROLLEASY 2

+ FINISHES

- Sturdy end-stands thanks to materials (lacquered aluminium) and components carefully selected for a perfect stability and an optimal rending.
- Simple in its conception to fit will all environments.

CUSTOMISABLE

- 3 versions available: electric, solar and manual.
- Customised end-stands for a perfect integration in the garden (from our collection).


























1 END-STANDS

· Lacquered aluminium end-stands.

ANODISED TUBE

MOTORISATION (for electric and solar versions)

- 12 V low voltage electric tubular motor.
- The lifetime of the motor is longer thanks to the bearings which support the tube and therefore the weight of the cover.
- Control box with a 200 VA transformer, protected by a magnetic-thermal circuit breaker.

Controlled by key switch.

4 LOCKING KITS

(5) SLATS

• Solar polycarbonate slats or opaque 69 PVC slats.

Your slats choice

All our slats have a quality finish and are compliant with the NF P90-308 standard.

Solar polycarbonate slats











Crystal green

USEFUL TO KNOW

Choose solar polycarbonate slats to heat your pool water.

Opaque PVC slats











DON'T FORGET

Protect your slats from UVs and dirt

LivePool

(except solar version).

Opening and closing of the automatic cover with a smartphone

thanks to the LivePool application

with the IVERNEA winter shift or the IVERNEA PLUS 4-season protective





The Rolleasy 2 cover is a swimming pool safety cover designed to prevent children under 5 years of age from accessing the pool. This product complies with the standard NF P90-308. It is no substitute for common sense or individual responsability. It is not intended either to be a substitute for parental and/or adult supervision, which is the essential factor for the protection of young childrens. A child can get drawned within less than 3 minutes; no type of protection will ever replace the vigilance and supervision of responsible adults.

Warranty: 2 years for the reel system and 2 years for the motor. 3 years for opaque PVC slats and 5 years for solar polycarbonate slats, in accordance with our general sales terms.

Order form: to have a cover correctly adjusted to the pool, it is essential to provide a drawing of the pool with measurements taken every 1 meter. In accordance with the standard NF P90-308, the gap between the inside of the pool and the edge of the cover must be less than 70 mm.

Operating time: for a pool of $5.00 \times 10.00 \, \text{m}$: 3 minutes for the automatic opening or closing and 30 secondes for the locking or unlocking of the safety kits. One person only can do the opening and closing of the Rolleasy 2.

Use: for all seasons. For a proper functioning, maintain a constant water level corresponding to a normal filtration of the pool. It is essential to have a water level regulator. The water level have to comply with the technical notice.

Use limits: The installation of an automatic DEL cover on overflow pools and/or with a stair along the length (detechable side stair) does not comply with the standard NF P90-308. Another safety device should be used in that case. Unless otherwise specified by the manufacturer, under water alarms are not compatible with DEL covers.

Wintering: the swimming pool must be wintered on the basis of its geographical location. Without lowering the water level, close the cover to its safety position and where applicable install a wintering net to protect the cover. If the water level is lowered so that the wall units are above the waterline, roll the cover in and secure the pool using a winter safety cover.

Packing list: for a swimming pool measuring 5.00 \times 10.00 m. Slats: 5 packages: 5.10 \times 0.25 \times 0.20 m - 250 kg / Tube: 1 package: 5.30 \times 0.20 \times 0.20 m - 30 kg / End-stands: 1 pallet: 0.50 \times 0.45 \times 0.35 m - 20 kg / Total weight: 300 kg.

Manufacturer: DEL SAS - ZA La Croix Rouge 35530 Brécé - France / www.del-piscine.fr



CF GROUP - DEL SAS - ZA LA CROIX ROUGE - 35530 BRÉCÉ - FRANCE